



# **PRICE LIST**

JULY 2023





# LIFT M

# **QUICK PUMP SELECT**

4CSS7-31 3000w pg 24

4CSS7-31 3000w pg 24

4CSS7-31 3000w pg 24

4HRH2200 pg 12

130

4CSS7-31 3000w pg 24

4CSS7-31 3000w pg 24

4HRH2200 pg 12

140

Average litres per day based on 6 pumping hours. Approximately 20% more water in summer, 20% less in winter.



### **ABOUT BW SOLAR**

BW Solar is the company behind the design, development & distribution of Waterboy products We're a family of farmers, drillers and pump technicians who recognised 20 years ago there needed to be a better way to pump water in rural and remote areas. So we got stuck in the only way we knew how - using our experience on the land to source and manufacture solutions that make sense out here. Today our pumps are in almost every corner of Australia and trusted by the biggest names in business.

As Australia is pushing more and more towards the protection of our environment, Waterboy is helping decarbonise our earth one pump at a time as we head towards a zero emissions future.

### **KEY SELLING POINTS**

- Environmentally friendly, helping decarbonise Australia.
- Perfect energy transition product to assist clients reduce CO<sup>2</sup> output.
- · Family owned business.
- A very good sized solar system for windmill and motorised pump replacements.
- · They are very reliable.
- · Pricing fits in below the major brands.
- · Helical rotor replacements are cheaper and easy to repair.
- · Systems are plug & play and very easy to install.
- You can keep a couple in stock and slot into jobs as required.
- · You don't need an app to operate.
- Systems come with 3 years warranty.

### **PRICING**

All pricing is RRP and does not include wholesale discount or GST.

### SYSTEM PACKING & SHIPPING

Complete kits include all the hardware for the pump system. You only need to supply a few fittings, poly pipe and concrete to complete installation.

Shipping rates as follows:

- XFREX1 200w, 300w and 400w systems \$300+GST
- XFREX2 800w and 1100w systems \$500+GST
- XFREX3 Bigger systems are quoted per application

Drive packs, is the pump, motor & controller only, does NOT include solar panels, framing or any accessories:

- XFREX4 Single drive pack \$100+GST
- XFREX5 10 x Drive packs \$500+GST

### NO DISCOUNT APPLIES TO FREIGHT

### **PUMP SIZING**

For product longevity, BW Solar strongly recommend upsizing the pumping system if operating close to the limit of the pump systems lift or flow rate capability. Operating above the pumps capabilities will reduce life and increase chance of failure due to stress on the entire system.

### WARRANTY

Waterboy pumps have averaged less than 1.5% warranty return rates over the last 5 years, as of 1st July 2023 warranty is increasing to 3 years on complete systems. All drive packs have a 2 year warranty.



Drive Pack







### **RETURN POLICY**


Please contact us prior to any return of goods to obtain authorisation.

Goods ordered and shipped but then returned (other than faulty goods) must be received back within 21 days of original shipment, in unused/ undamaged condition, in original packaging Customer to pay return freight costs and 20% restocking fee. Pump parts ordered (rotor/stator or impellers) are non-returnable.



# HELICAL ROTOR PUMP SYSTEMS

# The most efficient, robust and cost effective pump



Bore Kit with 35m cable/ Dam Kit with 35m cable System Wattage Helical Rotor / High Head Pump Diameter

### 3HR200-B35 / 3HR200-D35

3" Diameter

HR - Helical Rotor pump end

200 - 200w of solar power

B35 - Bore kit with 35m power, low water and SS safety cabling

D35 - Dam kit with 35m power cable and SS safety cable

### 4HRH1100-B40 / 4HRH1100-D40

4" Diameter

HRH - High Head Helical Rotor pump end

1100 - 1100w of solar power

B40 - Bore kit with 40m power, low water and SS safety cabling

D40 - Dam kit with 40m power cable and SS safety cable

### Add extra cable to any pump system:

6000B bore pump extra cabling (power, low water & ss safety cable) \$16/m+GST 6000D dam pump system extra (Power and SS safety cable) \$12/m+GST

### PERFORMANCE CHARTS

3HR200							
TDH	L/MIN	L/DAY					
5	17	6120					
10	16	5760					
15	14	5040					
20	12	4320					
25	10	3600					
30	8	2880					

TDH - Total Dynamic Head is the calculation of vertical meters lift plus any friction loss in the delivery pipe. A bigger pipe size will help reduce friction and increase the pumps longevity.

L/DAY - Performance based on 6 peak sun hours of pumping. Summer months you can expect 20% more water per day and winter months 20% less.



### Helical Rotor (HR) solar pump systems include

- Drive Pack pump, motor, controller
- Heavy duty cyclone rated pole mount frame
- Mono crystalline solar panels
- Bore or Dam mounting accessory kit
- 35m or 40m Cabling set (power, low water & SS safety)

	3HR200		3HR200 3HR300		3HR	H400
TDH	L/MIN	L/DAY	L/MIN	L/DAY	L/MIN	L/DAY
5	17	6,120	26	9,360	32	11,520
10	16	5,760	25	9,000	31	11,160
15	14	5,040	24	8,640	30	10,800
20	12	4,320	22	7,920	29	10,440
25	10	3,600	20	7,200	28	10,080
30	8	2,880	18	6,480	27	9,720
40			13	4,680	23	8,280
50			8	2,880	20	7,200
60					15	5,400
70					12	4,320
RRP	\$4	312	\$5.	022	\$5.	503



TDH	L/MIN	L/DAY	L/MIN	L/DAY	L/MIN	L/DAY	L/MIN	L/DAY
10	47	16,920	38	13,680	51	18,360	61	21,960
20	37	13,320	37	13,320	50	18,000	61	21,960
30	27	9,720	36	12,960	47	16,920	61	21,960
40	18	6,480	34	12,240	46	16,560	60	21,600
50			33	11,880	44	15,840	55	19,800
60			30	10,800	42	15,120	50	18,000
70			28	10,080	39	14,040	45	16,200
80			26	9,360	36	12,960	40	14,400
90			15	5,400	33	11,880	38	13,680
100					28	10,080	34	12,240
110					25	9,000	30	10,800
120					20	7,200	27	9,720
130							23	8,280
140							19	6,840
RRP	<b>\$5,</b>	926	\$6,	735	\$7,220		\$8,	633





- Dry run protection
- Bore cap or Dam float
- Spare helical rotor
- Easy DIY installation manual





### **SOLAR PUMP SYSTEM INCLUDES:**



3HRSS Pump, Motor, and Controller



35m of Power Cable low water probe & safety cabling



**Heavy Duty** Cyclone Kated Pole Mount Frame



2x105w Mono Crystalline Solar Panels



Bore Cap or Dam Float



Low water protection (bore kit only)

### **ACCESSORIES**



Tank full switch inc 20m cable \$165+GST



**Pressure Switch** 12 bar inc gauge & fittings \$275+GST



Double acting float valve For use with Pressure Switch - \$275+GST



Anode \$120+GST



**Shipping Dimensions** 1x Crate 175 x 55 x 65cm @ 125kg



### WATERBOY 3HR300 3" Helical Rotor Solar Pumping System

### **FEATURES**

- Brushless DC motor
- Integrated Soft start & MPPT
- Adjustable Speed & Timer Control
- All Stainless Steel
- High Efficiency

### **BENEFITS**

- Lift up to 50m
- Flow rate up to 9,360 L/day
- Simple installation
- Maintenance-free
- High reliability & life expectancy

\$5,022+gst

Delivery \$300+GST

Bore part number: 3HR300-B35 Dam Floating part number: 3HR300-D35 Nationwide Delivery part number: XFREX1



### 3HR300

	2								
TDH		L/MIN	L/DAY						
	5	26	9,360						
	10	25	9,000						
	15	24	8,640						
	20	22	7,920						
	25	20	7,200						
	30	18	6,480						
	40	13	4,680						
	50	8	2,880						

### **SOLAR PUMP SYSTEM INCLUDES:**



3HRSS Pump, Motor, and Controller



35m of Power Cable low water probe & safety cabling



Heavy Duty Cyclone Rated Pole Mount Frame



3x105w Mono Crystalline Solar Panels



Bore Cap or Dam Float



Low water protection (bore kit only)

### **ACCESSORIES**



Tank full switch inc 20m cable \$165+GST



Pressure Switch 12 bar inc gauge & fittings \$275+GST



Double acting float valve For use with Pressure Switch - \$275+GST




Anode \$120+GST




Shipping Dimensions 1x Crate 175 x 55 x 65cm @ 135kg





### **SOLAR PUMP SYSTEM INCLUDES:**







40m of Power Cable low water probe & safety cabling



Heavy Duty Cyclone Rated Pole Mount Frame



4x105w Mono Crystalline Solar Panels



70

12

Bore Cap or Dam Float



4,320

Low water protection (bore kit only)

### **ACCESSORIES**



Tank full switch inc 20m cable \$165+GST



Pressure Switch 12 bar inc gauge & fittings \$275+GST



Double acting float valve For use with Pressure Switch - \$275+GST



Anode \$120+GST



Shipping Dimensions
1x Crate 175 x 55 x 65cm @ 150kg



### **WATERBOY 4HR400** 4" Helical Rotor **Solar Pumping System**

### **FEATURES**


- Brushless DC motor
- Integrated Soft start & MPPT
- Adjustable Speed & Timer Control
- All Stainless Steel
- High Efficiency

### **BENEFITS**

- Lift up to 40m
- Flow rate up to 16,920 L/day
- Simple installation
- Maintenance-free
- High reliability & life expectancy

Delivery **\$300**+GST

Bore part number: 4HR400-B40 Dam Floating part number: 4HR400-D40 Nationwide Delivery part number: XFREX1



TDH	L/MIN	L/DAY
10	47	16,920
20	37	13,320
30	27	9,720
40	18	6,480

### **SOLAR PUMP SYSTEM INCLUDES:**



4HRSS Pump, Motor, and Controller



40m of Power Cable low water probe & safety cabling



**Heavy Duty** Cyclone Rated Pole Mount Frame



4x105w Mono Crystalline Solar Panels



Bore Cap or Dam Float



Low water protection (bore kit only)

### **ACCESSORIES**



Tank full switch inc 20m cable \$165+GST



**Pressure Switch** 12 bar inc gauge & fittings \$275+GST



Double acting float valve For use with Pressure Switch - \$275+GST



Anode \$120+GST



**Shipping Dimensions** 1x Crate 175 x 55 x 65cm @ 165kg



### **WATERBOY 4HRH800** 4" Helical Rotor **Solar Pumping System**

### **FEATURES**

- Brushless DC motor
- Integrated Soft start & MPPT
- Adjustable Speed & Timer Control
- All Stainless Steel
- High Efficiency

### **BENEFITS**

- Lift up to 90m
- Flow rate up to 13,680 L/day
- Simple installation
- Maintenance-free
- High reliability & life expectancy

735+GST

**Delivery \$500**+GST

Bore part number: 4HRH800-B40 Dam Floating part number: 4HRH800-D40 Nationwide Delivery part number: XFREX2



### **4HRH800**

TDH	L/MIN	L/DAY
10	38	13,680
20	37	13,320
30	36	12,960
40	34	12,240
50	33	11,880
60	30	10,800
70	28	10,080
80	26	9,360
90	15	5,400

### **SOLAR PUMP SYSTEM INCLUDES:**




4HRSS-H Pump, Motor, and Controller



40m of Power Cable low water probe & safety cabling



**Heavy Duty** Cyclone Kated Pole Mount Frame



3x330w Mono Crystalline Solar Panels



Bore Cap or Dam Float



Low water protection (bore kit only)

### **ACCESSORIES**



Tank full switch inc 20m cable \$165+GST



**Pressure Switch** 12 bar inc gauge & fittings \$275+GST



Double acting float valve For use with Pressure Switch - \$275+GST





**Shipping Dimensions** \$120+GST 1x Crate 210 x 100 x 55cm @ 195kg







4HRSS-H Pump, Motor, and Controller



40m of Power Cable low water probe & safety cabling



**Heavy Duty** Cyclone Rated Pole Mount Frame



4x330w Mono Crystalline Solar Panels



Bore Cap or Dam Float



Low water protection (bore kit only)

### **ACCESSORIES**



Tank full switch inc 20m cable \$165+GST



**Pressure Switch** 12 bar inc gauge & fittings \$275+GST




Double acting float valve For use with Pressure Switch - \$275+GST





**Shipping Dimensions** \$120+GST 1x Crate 210 x 100 x 60cm @ 215kg







4HRSS-H Pump, Motor, and Controller



40m of Power Cable low water probe & safety cabling



Heavy Duty Cyclone Rated Pole Mount Frame



8x330w Mono Crystalline Solar Panels



Bore Cap or Dam Float



Low water protection (bore kit only)

### **ACCESSORIES**



Tank full switch inc 20m cable \$165+GST



Pressure Switch 12 bar inc gauge & fittings \$275+GST



Double acting float valve For use with Pressure Switch - \$275+GST



Anode \$120+GST




Shipping Dimensions 1x Crate 290 x 55 x 65cm @ 230kg 1x Pallet 170 x 115 x 43cm @ 170kg



# CENTRIFUGAL PUMP SYSTEMS

# High flow medium lift applications



### 4C781100-B40 / 4C781100-D40

- 4" Diameter
- C Centrifugal pump end
- 7 Rated flow rate m3/hr
- 8 Number of impellers

1100 – 1100w of solar power supplied with system

B40 - Bore kit with 40m power, low water and SS safety cabling

D40 - Dam kit with 40m power cable and SS safety cable

### PERFORMANCE CHARTS


	<b>4C781100</b>								
-	TDH	L/MIN	L/DAY						
	5	100	36,000						
	10	95	34,200						
	15	90	32,400						
	20	85	30,600						
	25	70	25,200	ı					
	30	60	21,600	ı					
	40	40	14,400						

TDH - Total Dynamic Head

is the calculation of vertical meters lift plus any friction loss in the delivery pipe. A bigger pipe size will help reduce friction and increase the pumps longevity.

L/DAY - Performance based on 6 peak sun hours of pumping. Summer months you can expect 20% more water per day and winter months 20% less.









40m Power Cable low water probe & safety cabling



- Dry run protection
- · Bore cap or Dam float
- Easy DIY installation manual





### **FEATURES**

- Brushless DC motor
- Integrated Soft start & MPPT
- Adjustable Speed & Timer Control
- All Stainless Steel
- High Efficiency

### **BENEFITS**

- Lift up to 20m
- Flow rate up to 15,120 L/day
- Simple installation
- Maintenance-free
- · High reliability & life expectancy

\$6,375+gst

Delivery \$300+GST

Bore part number: 4C48400-B40
Dam Floating part number: 4C48400-D40
Nationwide Delivery part number: XFREX1



### **SOLAR PUMP SYSTEM INCLUDES:**



4CSS Pump, Motor, and Controller



40m of Power Cable low water probe & safety cabling



Heavy Duty Cyclone Rated Pole Mount Frame



4x105w Mono Crystalline Solar Panels



Bore Cap or Dam Float



L/DAY

15,120

14,760

12,240

10,080

4C48400

42

41

34

28

TDH L/MIN

5

10

15 20

Low water protection (bore kit only)

### **ACCESSORIES**



Tank full switch inc 20m cable \$165+GST



Pressure Switch 12 bar inc gauge & fittings \$275+GST



Double acting float valve For use with Pressure Switch - \$275+GST



Anode \$120+GST



Shipping Dimensions
1x Crate 175 x 55 x 65cm @ 165kg





### **SOLAR PUMP SYSTEM INCLUDES:**



4CSS Pump, Motor, and Controller



40m of Power Cable low water probe & safety cabling



**Heavy Duty** Cyclone Rated Pole Mount Frame



4x330w Mono Crystalline Solar Panels



Bore Cap or Dam Float



Low water protection (bore kit only)

### **ACCESSORIES**



Tank full switch inc 20m cable \$165+GST



**Pressure Switch** 12 bar inc gauge & fittings \$275+GST



Double acting float valve For use with Pressure Switch - \$275+GST



Anode



**Shipping Dimensions** \$120+GST 1x Crate 210 x 100 x 60cm @ 230kg



# **WATERBOY 4C5121100** 4" Centrifugal Solar Pumping System

### **FEATURES**

- Brushless DC motor
- Integrated Soft start & MPPT
- Adjustable Speed & Timer Control
- All Stainless Steel
- High Efficiency

### **BENEFITS**

- Lift up to 40m
- Flow rate up to 21,600 L/day
- Simple installation
- Maintenance-free
- High reliability & life expectancy

Delivery **\$500**+GST

Bore part number: 4C5121100-B40 Dam Floating part number: 4C5121100-D40 Nationwide Delivery part number: XFREX2



TDH	L/MIN	L/DAY
5	60	21,600
10	60	21,600
15	55	19,800
20	52	18,720
25	48	17,280
30	45	16,200
40	36	12,960

### **SOLAR PUMP SYSTEM INCLUDES:**



4CSS Pump, Motor, and Controller



40m of Power Cable low water probe & safety cabling



**Heavy Duty** Cyclone Kated Pole Mount Frame



4x330w Mono Crystalline Solar Panels



Bore Cap or Dam Float



Low water protection (bore kit only)

### **ACCESSORIES**



Tank full switch inc 20m cable \$165+GST



**Pressure Switch** 12 bar inc gauge & fittings \$275+GST



Double acting float valve For use with Pressure Switch - \$275+GST





**Shipping Dimensions** \$120+GST 1x Crate 210 x 100 x 60cm @ 230kg









**Heavy Duty** Cyclone Rated Pole Mount Frame



4x330w Mono Crystalline Solar Panels



Bore Cap or Dam Float



Low water protection (bore kit only)

### **ACCESSORIES**



Tank full switch inc 20m cable \$165+GST



**Pressure Switch** 12 bar inc gauge & fittings \$275+GST



Double acting float valve For use with Pressure Switch - \$275+GST




Anode



**Shipping Dimensions** \$120+GST 1x Crate 210 x 100 x 60cm @ 230kg





- Integrated Soft start & MPPT
- Adjustable Speed & Timer Control
- All Stainless Steel
- High Efficiency

### **BENEFITS**

- Lift up to 60m
- Flow rate up to 46,800 L/day
- Simple installation
- Maintenance-free
- High reliability & life expectancy

for delivery rates

Bore part number: 4C782200-B40 Dam Floating part number: 4C782200-D40



#### L/MIN **TDH** L/DAY 130 46,800 10 20 43,200 120 30 100 36,000 40 90 32,400 50 80 28,800 60 70 25,200

### **SOLAR PUMP SYSTEM INCLUDES:**



4CSS Pump, Motor, and Controller



40m of Power Cable low water probe & safety cabling



**Heavy Duty** Cyclone Rated Pole Mount Frame



8x330w Mono Crystalline Solar Panels



Bore Cap or Dam Float



Low water protection (bore kit only)

### **ACCESSORIES**



Tank full switch inc 20m cable \$165+GST



**Pressure Switch** 12 bar inc gauge & fittings \$275+GST



Double acting float valve For use with Pressure Switch - \$275+GST




Anode \$120+GST



**Shipping Dimensions** 1x Crate 440 x 60 x 65cm @ 280kg 1x Pallet 200 x 115 x 45cm @ 190kg





### **SOLAR PUMP SYSTEM INCLUDES:**



4CSS Pump, Motor, and Controller



40m of Power Cable low water probe & safety cabling



**Heavy Duty** Cyclone Rated Pole Mount Frame



8x330w Mono Crystalline Solar Panels



Bore Cap or Dam Float



Low water protection (bore kit only)

### **ACCESSORIES**



Tank full switch inc 20m cable \$165+GST



**Pressure Switch** 12 bar inc gauge & fittings \$275+GST



Double acting float valve For use with Pressure Switch - \$275+GST



Anode \$120+GST



**Shipping Dimensions** 1x Crate 440 x 60 x 65cm @ 280kg 1x Pallet 200 x 115 x 45cm @ 190kg



# WATERBOY 4C1262200 4" Centrifugal Solar Pumping System

### **FEATURES**

- Brushless DC motor
- Integrated Soft start & MPPT
- Adjustable Speed & Timer Control
- All Stainless Steel
- High Efficiency


### **BENEFITS**

- Lift up to 40m
- Flow rate up to 72,000 L/day
- Simple installation
- Maintenance-free
- · High reliability & life expectancy

\$**9,248**+gst

Contact us for delivery rates

Bore part number: 4C1262200-B40 Dam Floating part number: 4C1262200-D40



### **SOLAR PUMP SYSTEM INCLUDES:**



4CSS Pump, Motor, and Controller



40m of Power Cable low water probe & safety cabling



Heavy Duty Cyclone Rated Pole Mount Frame



8x330w Mono Crystalline Solar Panels



10

20

30

40

200

160

120

90

Bore Cap or Dam Float



72.000

57,600

43,200

32,400

Low water protection (bore kit only)

### **ACCESSORIES**



Tank full switch inc 20m cable \$165+GST



Pressure Switch 12 bar inc gauge & fittings \$275+GST



Double acting float valve For use with Pressure Switch - \$275+GST



Anode \$120+GST



Shipping Dimensions 1x Crate 440 x 60 x 65cm @ 280kg 1x Pallet 200 x 115 x 45cm @ 190kg







5CSS Pump, Motor, and Controller



40m of Power Cable low water probe & safety cabling



Heavy Duty Cyclone Rated Pole Mount Frame



8x330w Mono Crystalline Solar Panels



Bore Cap or Dam Float



Low water protection (bore kit only)

### **ACCESSORIES**



Tank full switch inc 20m cable \$165+GST



Pressure Switch 12 bar inc gauge & fittings \$275+GST



Double acting float valve For use with Pressure Switch - \$275+GST



Anode \$120+GST




Shipping Dimensions 1x Crate 440 x 60 x 65cm @ 280kg 1x Pallet 200 x 115 x 45cm @ 190kg



# 3000W CENTRIFUGAL PUMP SYSTEMS

# High flow and high lift applications



### 4C20103000B / 4C20103000D

4" Diameter

C - Centrifugal pump end

20 - Rated flow rate m3/hr

10 – Number of impellers

3000 - 3000w of solar power supplied with system

B - 6000B bore pump extra cabling (power, low water & ss safety cable) \$16/m+GST

D – 6000D dam pump system extra (Power and SS safety cable) \$12/m+GST

### PERFORMANCE CHARTS

<b>4C20103000</b>							
TDH	L/MIN	L/DAY					
10	291	104,760					
20	250	90,000					
30	200	72,000					
40	165	59,400					
50	110	39,600					
60	65	23,400					

TDH - Total Dynamic Head is the calculation of vertical meters lift plus any friction loss in the delivery pipe. A bigger pipe size will help reduce friction and increase the pumps longevity.

L/DAY - Performance based on 6 peak sun hours of pumping. Summer months you can expect 20% more water per day and winter months 20% less.



# 3000W Centrifugal (C) solar pump systems include

- Drive Pack pump, motor, controller
- Heavy duty cyclone rated pole mount frame
- 3000W Mono crystalline solar panels
- Bore or Dam mounting accessory kit
- DC isolator

	4C446	63000	<b>4C7</b> 3	<b>13000</b>	4C12	183000	4C201	.03000	<b>5C60</b> 2	23000
TDH	L/MIN	L/DAY	L/MIN	L/DAY	L/MIN	L/DAY	L/MIN	L/DAY	L/MIN	L/DAY
10	66	23,760	121	43,560	200	72,000	291	104,760	260	93,600
20	65	23,400	116	41,760	183	65,880	250	90,000		
30	63	22,680	110	39,600	170	61,200	200	72,000		
40	61	21,960	105	37,800	158	56,880	165	59,400		
50	60	21,600	100	36,000	140	50,400	110	39,600		
60	59	21,240	93	33,480	125	45,000	65	23,400		
70	58	20,880	88	31,680	111	39,960				
80	56	20,160	85	30,600	100	36,000				
90	53	19,080	80	28,800	83	29,880				
100	50	18,000	75	27,000	65	23,400				
110	48	17,280	70	25,200	50	18,000				
120	45	16,200	63	22,680	33	11,880				
130	41	14,760	58	20,880	16	5,760				
140	38	13,680	53	19,080						
150	35	12,600	42	15,120						
160	33	11,880	38	13,680						
170	28	10,080	28	10,080						
180	26	9,360	24	8,640						
190	25	9,000	16	5,760						
200	23	8,280	8	2,880						
210	20	7,200								
220	16	5,760								
230	15	5,400								
240	11	3,960								
250	8	2,880								
RRP	<b>\$11</b> ,	590	\$11	.,590	\$11	L,590	\$11	,590	\$11	,590









- Dry run protection
- Bore cap or Dam float
- Easy DIY installation manual



### **WATERBOY 4C7313000** 4" Centrifugal **Solar Pumping System**

### **FEATURES**

- Brushless DC motor
- Integrated Soft start & MPPT
- Adjustable Speed & Timer Control
- All Stainless Steel
- High Efficiency

### **BENEFITS**

- Lift up to 200m
- Flow rate up to 43,560 L/day
- Simple installation
- Maintenance-free
- High reliability & life expectancy



Bore part number: 4C7313000B Dam Floating part number: 4C7313000D Bore pump extra cabling: 6000B Dam pump extra cabling: 6000D



### **4C7313000**

TDH	L/MIN	L/DAY
50	100	36,000
60	93	33,480
70	88	31,680
80	85	30,600
90	80	28,800
100	75	27,000
110	70	25,200
120	63	22,680
130	58	20,880
140	53	19,080
150	42	15,120
160	38	13,680
170	28	10,080
180	24	8,640
190	16	5,760
200	8	2,880

# **SOLAR PUMP SYSTEM INCLUDES:**

for delivery rates



4CSS Pump, Motor, and Controller



Power, Low Water and SS Safety Cable Bore \$16p/m / Dam \$12p/m



**Heavy Duty** Cyclone Rated Pole Mount Frame



8x430w Mono Crystalline Solar Panels



Bore Cap or Dam Float



Low water protection (bore kit only)

### **ACCESSORIES**



Tank full switch inc 20m cable \$165+GST



**Pressure Switch** 12 bar inc gauge & fittings \$275+GST



Double acting float valve For use with Pressure Switch - \$275+GST




Anode \$120+GST



**Shipping Dimensions** 1x Crate 440 x 60 x 65cm @ 280kg 1x Pallet 200 x 115 x 45cm @ 190kg





### **SOLAR PUMP SYSTEM INCLUDES:**



4CSS Pump, Motor, and Controller



Power, Low Water and SS Safety Cable Bore \$16p/m / Dam \$12p/m



Heavy Duty Cyclone Rated Pole Mount Frame



8x430w Mono Crystalline Solar Panels



130

16

Bore Cap or Dam Float



5,760

Low water protection (bore kit only)

### **ACCESSORIES**



Tank full switch inc 20m cable \$165+GST



Pressure Switch 12 bar inc gauge & fittings \$275+GST



Double acting float valve For use with Pressure Switch - \$275+GST



Anode \$120+GST



Shipping Dimensions 1x Crate 440 x 60 x 65cm @ 280kg 1x Pallet 200 x 115 x 45cm @ 190kg



### WATERBOY 4C4463000 4" Centrifugal Solar Pumping System

### **FEATURES**

- Brushless DC motor
- Integrated Soft start & MPPT
- Adjustable Speed & Timer Control
- All Stainless Steel
- High Efficiency

### **BENEFITS**

- Lift up to 250m
- Flow rate up to 23,760 L/day
- Simple installation
- Maintenance-free
- · High reliability & life expectancy

\$11,590+GST

for delivery rates

Bore part number: 4C4463000B Dam Floating part number: 4C4463000D Bore pump extra cabling: 6000B Dam pump extra cabling: 6000D



### 4C4463000

TDH	L/MIN	L/DAY
100	50	18,000
110	48	17,280
120	45	16,200
130	41	14,760
140	38	13,680
150	35	12,600
160	33	11,880
170	28	10,080
180	26	9,360
190	25	9,000
200	23	8,280
210	20	7,200
220	16	5,760
230	15	5,400
240	11	3,960
250	8	2,880

### **SOLAR PUMP SYSTEM INCLUDES:**




4CSS Pump, Motor, and Controller



Power, Low Water and SS Safety Cable Bore \$16p/m / Dam \$12p/m



Heavy Duty Cyclone Rated Pole Mount Frame



8x430w Mono Crystalline Solar Panels



Bore Cap or Dam Float



Low water protection (bore kit only)

### **ACCESSORIES**



Tank full switch inc 20m cable \$165+GST



Pressure Switch 12 bar inc gauge & fittings \$275+GST



Pouble acting float valve
For use with Pressure
Switch - \$275+GST



Anode \$120+GST



Shipping Dimensions 1x Crate 440 x 60 x 65cm @ 280kg 1x Pallet 200 x 115 x 45cm @ 190kg





### **SOLAR PUMP SYSTEM INCLUDES:**



4CSS Pump, Motor, and Controller



Power, Low Water and SS Safety Cable Bore \$16p/m / Dam \$12p/m



Heavy Duty Cyclone Rated Pole Mount Frame



8x430w Mono Crystalline Solar Panels



Bore Cap or Dam Float



Low water protection (bore kit only)

### **ACCESSORIES**



Tank full switch inc 20m cable \$165+GST



Pressure Switch 12 bar inc gauge & fittings \$275+GST



Double acting float valve For use with Pressure Switch - \$275+GST



Anode \$120+GST



Shipping Dimensions 1x Crate 440 x 60 x 65cm @ 280kg 1x Pallet 200 x 115 x 45cm @ 190kg



# WATERBOY 5C6023000 5" Centrifugal Solar Pumping System

### **FEATURES**

- Brushless DC motor
- Integrated Soft start & MPPT
- Adjustable Speed & Timer Control
- All Stainless Steel
- High Efficiency

### **BENEFITS**

- Lift up to 10m
- Flow rate up to 93,600 L/day
- Simple installation
- Maintenance-free
- High reliability & life expectancy

\$11,590+gst

Contact us for delivery rates

Bore part number: 5C6023000B Dam Floating part number: 5C6023000D Bore pump extra cabling: 6000B Dam pump extra cabling: 6000D



### **SOLAR PUMP SYSTEM INCLUDES:**




5CSS Pump, Motor, and Controller



Power, Low Water and SS Safety Cable Bore \$16p/m / Dam \$12p/m



Heavy Duty Cyclone Rated Pole Mount Frame



8x430w Mono Crystalline Solar Panels



Bore Cap or Dam Float



L/DAY

93.600

L/MIN

260

TDH

Low water protection (bore kit only)

### **ACCESSORIES**



Tank full switch inc 20m cable \$165+GST



Pressure Switch 12 bar inc gauge & fittings \$275+GST



Double acting float valve For use with Pressure Switch - \$275+GST



Anode \$120+GST




Shipping Dimensions 1x Crate 440 x 60 x 65cm @ 280kg 1x Pallet 200 x 115 x 45cm @ 190kg



# SOLAR DC DRIVE PACKS

### Pump motor and controller only

Does not include solar panels or framing



These drive packs are used to make our complete systems, ie:

- 3HR200 utilises 3HRSS drivepack
- 3HRH400 uses the 3HRSS-H drivepack
- 4C782200 uses the 4CSS7-8 drive pack














# 3" Helical Rotor Drive Packs







### **3HRSS**

3" helical rotor submersible drive pack inc 210w motor, controller, spare helical rotor and 3m motor lead.

\$1,753+gst

### **3HRSS-35**

3" helical rotor submersible drive pack inc 210w motor, controller, spare helical rotor and pump fitted with 35m power cable.

\$1,935+gst

### 3HRSS-H

3" helical rotor submersible drive pack inc 500w motor, controller, spare helical rotor and 3m motor lead.

\$2,026+gst

### 3HRSS-H-40

3" helical rotor submersible drive pack inc 500w motor, controller, spare helical rotor and pump fitted with 40m power cable.

\$2,205+gst


\*\*\* Does not include solar panels\*\*\*

### 3HRSS-35 1x330w

TDH	L/MIN	L/DAY
5	16	5,760
10	16	5,760
15	15	5,400
20	15	5,400
25	14	5,040
30	13	4,680
40	11	3,960

### **3HRSS-H-40** 2x330w

TDH	L/MIN	L/DAY
10	27	9,720
20	25	9,000
30	24	8,640
40	22	7,920
50	19	6,840
60	17	6,120
70	15	5,400
80	11	3,960



# 4" Helical Rotor Drive Packs







### **4HRSS**

4" helical rotor submersible drive pack inc 500w motor, controller, spare helical rotor and 3m motor lead.

### \$2.195+GST

### **4HRSS-40**

4" helical rotor submersible drive pack inc 500w motor, controller, spare helical rotor and pump fitted with 40m power cable.

### \$2,384+gst

### 4HRSS-H

4" helical rotor submersible drive pack inc 1000w motor, controller, spare helical rotor and 3m motor lead.

### \$2,535+GST

### **4HRSS-H-40**

4" helical rotor submersible drive pack inc 1000w motor, controller, spare helical rotor and pump fitted with 40m power cable.

### \$2,856+gst

### 4HRSS-H-40 8x330w

44

42

36

33

28

25

15,840

15,120 14,040

12,960

11,880

10,080

9,000

7,200

50

60

70 80

90


100

110

120

TDH	L/MIN	L/DAY
40	60	21,600
50	55	19,800
60	50	18,000
70	45	16,200
80	40	14,400
90	38	13,680
100	34	12,240
110	30	10,800
120	27	9,720
130	23	8,280
140	19	6,840

<sup>\*\*\*</sup> Does not include solar panels\*\*\*









### 4CSS 4-8

4" C submersible drive pack including 500w motor and controller, Max 100 Voc.

\$2,245+gst

### 4CSS 5-12

4" C submersible drive pack including 1000w motor and controller, Max 200 Voc.

\$2,735+gst

### **4CSS 7-8**

4" C submersible drive pack including 1000w motor and controller, Max 200 Voc.

\$2,735+GST

\*\*\* Does not include solar panels\*\*\*

### **4CSS 12-6**

4" C submersible drive pack including 1000w motor and controller, Max 200 Voc.

\$2.840+gst

### 5CSS 28-2

5" C submersible drive pack including 1000w motor and controller, Max 200 Voc.

\$2,960+gst

### **4CSS 4-8** 4x105w

TDH	L/MIN	L/DAY
5	42	15,120
10	41	14,760
15	34	12,240
20	28	10,080

### 4CSS 7-8 8x330w

TDH	L/MIN	L/DAY
10	130	46,800
20	120	43,200
30	100	36,000
40	90	32,400
50	80	28,800
60	70	25,200

### 4CSS 12-6 8x330w

TDH	L/MIN	L/DAY
10	200	72,000
20	160	57,600
30	120	43,200
40	90	32,400

### **5CSS 28-2** 8x330w

TDH	L/MIN	L/DAY
10	260	93,600



**3kw Centrifugal (C) Drive Packs** 







### 4CSS 12-18

4" C submersible drive pack including 3000w motor and controller, Max 450 Voc.

\$3.690+gst

### 4CSS 20-10

4" C submersible drive pack including 3000w motor and controller, Max 450 Voc.

\$3,690+gst

### 4CSS 4-46

4" C submersible drive pack including 3000w motor and controller, Max 450 Voc.

\$3,690+gst

### 4CSS 7-31

4" C submersible drive pack including 3000w motor and controller, Max 450 Voc.

\$3,690+gst

### 4CSS 12-18 8x430w

TDH	L/MIN	L/DAY
10	200	72,000
20	183	65,880
30	170	61,200
40	158	56,880
50	140	50,400
60	125	45,000
70	111	39,960
80	100	36,000
90	83	29,880
100	65	23,400
110	50	18,000
120	33	11,880
130	16	5,760

### 4CSS 20-10 8x430w

TDH	L/MIN	L/DAY
10	291	104,760
20	250	90,000
30	200	72,000
40	165	59,400
50	110	39,600
60	65	23,400

L/MIN L/DAY

100	50	18,000
110	48	17,280
120	45	16,200
130	41	14,760
140	38	13,680
150	35	12,600
160	33	11,880
170	28	10,080
180	26	9,360
190	25	9,000
200	23	8,280
210	20	7,200
220	16	5,760
230	15	5,400
240	11	3,960
250	8	2,880

### 4CSS 7-31 8x430w

TDH	L/MIN	L/DAY
50	100	36,000
60	93	33,480
70	88	31,680
80	85	30,600
90	80	28,800
100	75	27,000
110	70	25,200
120	63	22,680
130	58	20,880
140	53	19,080
150	42	15,120
160	38	13,680
170	28	10,080
180	24	8,640
190	16	5,760
200	8	2,880

\*\*\* Does not include solar panels\*\*\*



# **Solar Surface Pump Drive Packs**





### WATERBOY SSP1500

1.5kW Solar Pool Pump Pump, Motor & Controller

### \$2,257+GST

### **BENEFITS**

- Zero energy costs provide a very fast return on Investment.
- Longer life expectancy than standard AC motors.
- · Quiet and efficient.
- Proven in service record.
- Fast and simple installation, direct replacement for an existing pool pump.
- Smart modular design for simple and cost effective servicing & repair.
- Maintenance-free.
- High reliability & life expectancy.
- 2-year warranty

### **FEATURES**

**Voltage:** 110V DC operation **Power:** 1500W 3 phase DC motor

Max Voltage: 200VDC

Max Flow Rate: 30m3/h / 180,000 L/day

Max Water Temp: 45°C Solar operation: 2000-2500W

Max Head: 15m Inlet/Outlet: 3" x 3"

### **PERFORMANCE**

M	L/MIN	L/DAY
2	500	180,000
5	440	158,400
10	300	108,000
15	180	64,800



### WATERBOY SSC3

500W Surface Pump Pump, Motor & Controller

### \$1,740+gst

### **BENEFITS**

- Zero energy costs provide a very fast return on Investment.
- Quiet and efficient.
- Smart modular design for simple and cost effective servicing & repair.
- Maintenance-free.
- High reliability & life expectancy.
- 2-year warranty

#### **FEATURES**

**Voltage:** 48V DC operation **Power:** 500W 3 phase DC motor

Max Voltage: 100VDC

Max Flow Rate: 3m3/h / 18,000 L/day

Max Water Temp: 45°C Solar operation: 500 - 800W

Max Lift: up to 40m Max Head: 15m Inlet/Outlet: 1" x 1"

# PERFORMANCE (2X330W)


M	L/MIN	L/DAY
5	45	16,200
10	40	14,400
15	33	11,880
20	25	9,000
30	15	5,400
40	10	3,600



# SOLAR OR 240V AC/DC DRIVE PACKS

# Pump AC/DC motor and switch only

Does not include solar panels or framing





## 4" AC/DC Submersible Pump 4CBW2.2-7-18



#### **FEATURES**

- Permanent magnet Brushless double shield motor with FOC function.
- Soft start operation function extends the life of the system.
- AC/DC wide voltage: 60-380VDC or 90-240VAC,50/60Hz.
- MPPT function for DC part, can achieve efficiency more than 99%.
- PFC (Power Factor Correction) function for AC can increase power factor over 0.99.

- No-load protection.
- · Reverse protection.
- Over load/under load protection.
- Over temperature protection.
- Over-current protection.
- · Over-voltage protection.
- Phase lack protection.
- · Locked rotor protection.

#### **BENEFITS**

- · Long life expectancy.
- Designed for use in remote & harsh Australian conditions.
- · High efficiency.
- · Fast & simple installation.
- · Cost effective spare parts philosophy.



	Model	Voltage	Po	ver	Max Flow Rate	Max Head	<b>Outlet Size</b>	Diameter
		(V)	kW	HP	(m³/h)	(m)	(In)	(In)
	4CBW2.2-7-18	DC: 60-380V AC: 90-240V/50Hz, 60Hz	2.2	3.0	6.5	140	2"	4"
/h)								
,							10m	
6							20m 30m	
							40m	
5							50m	
							60m 70m	
			/				70m 80m	
4							90m	
							100m	
3							110m	
							120m	
							130m	
2							140m	
1								
'								
0								



#### **ELECTRICAL PARAMETERS**

Power:	550w - 3000w
Current Range:	1.5-14A
Speed Range:	Max 3600 RPM
Insulation Class:	F
Protection Class:	IP 68
Maximum input voltage of the solar panel:	No more than 450Voc
Solar panel connection:	All in series

\$3,550+GST

Includes AC/DC Switch The pump has an external switch where AC power, DC power and pump can be connected to the switch and make automatic conversion. Water level sensor contacts to sense the water level and control the pump automatically.



## 4" AC/DC Submersible Pump 4CBW2.2-14-12



#### **FEATURES**

- Permanent magnet Brushless double shield motor with FOC function.
- Soft start operation function extends the life of the system.
- AC/DC wide voltage: 60-380VDC or 90-240VAC,50/60Hz.
- MPPT function for DC part, can achieve efficiency more than 99%.
- PFC (Power Factor Correction) function for AC can increase power factor over 0.99.


- · No-load protection.
- · Reverse protection.
- Over load/under load protection.
- · Over temperature protection.
- Over-current protection.
- · Over-voltage protection.
- · Phase lack protection.
- · Locked rotor protection.

#### **BENEFITS**

- Long life expectancy.
- Designed for use in remote & harsh Australian conditions.
- · High efficiency.
- · Fast & simple installation.
- · Cost effective spare parts philosophy.



Model	Voltage	Power		Max Flow Rate	Max Head	Outlet Size	Diameter
	(V)	kW	HP	(m³/h)	(m)	(In)	(In)
4CBW2.2-14-12	DC: 60-380V	2.2	3.0	14	165	2"	4"





#### **ELECTRICAL PARAMETERS**

Power:	550w - 3000w
Current Range:	1.5-14A
Speed Range:	Max 3600 RPM
Insulation Class:	F
Protection Class:	IP 68
Maximum input voltage of the solar panel:	No more than 450Voc
Solar panel connection:	All in series

\$3,550+GST

Includes AC/DC Switch The pump has an external switch where AC power, DC power and pump can be connected to the switch and make automatic conversion. Water level sensor contacts to sense the water level and control the pump automatically.



## 4" AC/DC Submersible Pump 4CBW2.2-19-17



#### **FEATURES**


- Permanent magnet Brushless double shield motor with FOC function.
- Soft start operation function extends the life of the system.
- AC/DC wide voltage: 60-380VDC or 90-240VAC,50/60Hz.
- MPPT function for DC part, can achieve efficiency more than 99%.
- PFC (Power Factor Correction) function for AC can increase power factor over 0.99.

- · No-load protection.
- · Reverse protection.
- Over load/under load protection.
- · Over temperature protection.
- · Over-current protection.
- Over-voltage protection.Phase lack protection.
- · Locked rotor protection.

#### **BENEFITS**

- · Long life expectancy.
- Designed for use in remote & harsh Australian conditions.
- · High efficiency.
- · Fast & simple installation.
- · Cost effective spare parts philosophy.







#### **ELECTRICAL PARAMETERS**

Power:	550w - 3000w
Current Range:	1.5-14A
Speed Range:	Max 3600 RPM
Insulation Class:	F
Protection Class:	IP 68
Maximum input voltage of the solar panel:	No more than 450Voc
Solar panel connection:	All in series

\$3,550+GST

Includes AC/DC Switch The pump has an external switch where AC power, DC power and pump can be connected to the switch and make automatic conversion. Water level sensor contacts to sense the water level and control the pump automatically.




## SOLAR PANELS SOLAR ARRAY FRAMES & SPARE PARTS





## **Monocrystalline Solar Panels**



## WB105M - \$286+GST

#### **FEATURES**

- 15.75% Maximum Module Efficiency
- 3 Years Limited Product Warranty
- 20 Years Performance Warranty

#### **BENEFITS**

- Performs under low light conditions
- Reliable High-Grade Materials
- Smart-Ready Design For Easy Upgrades

#### **PERFORMANCE**

Max Power	P <sub>max</sub>	105W
Max Power Tolerance	$\Delta P_{\text{max}}$	0~+3%
Max Power Voltage	$V_{mpp}$	17.5V
Max Power Current	Impp	6.0A
Open-Circuit Voltage	Voc	22.0V
Short-Circuit Current	Isc	6.45A
Module Efficiency	Eff.	15.75%


#### **WARRANTY**

3 years Warranty.

Performance guarantee: 10 years (90% power output)

20 years (80% power output)

Details according to warranty issued by BW Solar.



## WB340M - \$550+gst

#### **FEATURES**

- 19.32% Maximum Module Efficiency
- 12 Years Limited Product Warranty
- 25 Years Performance Warranty

#### **BENEFITS**

- Performs under low light conditions
- Reliable High-Grade Materials
- Smart-Ready Design For Easy Upgrades

#### **PERFORMANCE**

Max Power	P <sub>max</sub>	340W
Max Power Tolerance	$\Delta P_{max}$	0~+5%
Max Power Voltage	$V_{mpp}$	38.77V
Max Power Current	Impp	8.77A
Open-Circuit Voltage	Voc	46.91V
Short-Circuit Current	Isc	9.45A
Module Efficiency	Eff.	17.52%

#### **WARRANTY**

12 years Warranty.

Performance guarantee: 25 years

Details according to warranty issued by BW Solar.



## **Solar Array Frames**



#### **OVERVIEW**

The WATERBOY fixed solar arrays have been designed to work with the WATERBOY range of solar pump systems and solar panels.

The heavy duty cyclone rated, hot galvanised, steel mounting posts have upper and lower sections which bolt together. This increases portability and ease of installation.


The angle of the solar array can be adjusted in 5 steps between 10° and 50°.

#### **FEATURES**

- Cyclone rated
- Aluminium Components are 6005 T5
- Steel components are Q235 and are hot dipped gavanised
- Bolts are SS304
- Adjustable angle of array in 5 steps between 10° and 50°
- Clamps compatible with most 35mm solar modules

#### WARRANTY

Three years manufacturer's warranty against defects in material and workmanship, from date of installation.



#### **WATERBOY Mini**

2.3m wide (4x105w or 2x340w panels)

The Mini fixed array will hold up to 4 x 105w or 2 x 340w solar panels with a total of 2.39m wide.

Mounting clamps are suitable for panels that are 35mm thick.

#### \$1,155+gst

Part number: WB-Mini

#### **WATERBOY Midi**

4.4m wide (4x340w panels)

The Midi fixed array will hold up to 4 x 340w solar panels with a total of 4.4m wide.

Mounting clamps are suitable for panels that are 35mm thick.

\$1,672+GST

Part number: WB-Midi

#### **WATERBOY Maxi**

4m high x 4.4m wide (8x340w or 8x430w panels)

The Maxi fixed array will hold up to 8 panels with 2 strings of 4 @ 4.4m wide and 4m high.

Mounting clamps are suitable for panels that are 35mm thick.

\$2,530+gst

Part number: WB-MaxiXL



#### **WATERBOY** Tin Roof Mount

4.4m wide (4x340w panels)

The Tin roof mount kit will hold up to 4 x 340w solar panels with a total of 4.4m wide. Mounting clamps are suitable for panels that are 35mm thick.

\$300+gst

Part number: RMKIT





24 – 48V nominal, Max 100V DC pump controller suitable for use with 3HRSS, 3HRSS-H, 4HRSS & 4CSS4-8 pumps.

96 – 110V nominal, Max 200V DC pump controller suitable for use with 4HRSS-H and 1000w centrifugal pumps.

\$1,210+GST

300V nominal, Max 450V DC pump controller suitable for use with 3000w centrifugal pumps.

\$1,008+GST





PCB500 24 – 48V nominal, Max 100V DC

\$892+gst

\$1,760+gst



**PCB1000** 96 – 110V nominal, Max 200V DC

\$1,105+gst



## Pumps & Motors



#### **HELICAL ROTOR PUMPS & MOTORS**



2HRSS 370W 36V DC

Motor Only

**\$915** +gst

Part No. 237048



3HRSS 210W 36V DC

Motor Only

\$960 + GST

Part No. 321048



3HRSS-H 500W 48V DC

Motor Only

\$1.008 + GST

Part No. 350048



4HRSS 500W 48V DC

Motor Only

\$1.029 + GST

Part No. 450048



4HRSS-H 1000W 110V

Motor Only

\$**1.135** +gst

Part No. 41000110



2HRSS 370W 2" HR 36V DC

Submersible Pump & Motor

\$**1,290** + GST

Part No. 20370



3HRSS 210W 3" HR 36V DC

Submersible Pump & Motor

\$1,370 + GST

Part No. 30210



3HRSS-H 500W 3" HR 48V DC

Submersible Pump & Motor

\$**1,548** + GST

Part No. 30500



4HRSS 500W 4" HR 48V DC

Submersible Pump & Motor

\$1.548 +gst

Part No. 40500



4HRSS-H 1000W 4" HR 110V

Submersible Pump & Motor

\$1,760 +gst

Part No. 41000



3HRSS 210W

Helical Rotor Assembly

\$250 + GST

Part No. 30001



3HRSS-H 500W

Helical Rotor Assembly

\$250 + GST

Part No. 30002



4HRSS 500W

Helical Rotor Assembly

\$295 + GST

Part No. 40001



4HRSS-H 1000W

Helical Rotor Assembly

\$330 + GST

Part No. 40002



## Pumps & Motors



#### **CENTRIFUGAL PUMPS & MOTORS**



**500W** 4" C 48V DC

Motor Only

**\$1.050** +gst

Part No. 450048C



**1000W** 4" C 110V DC

Motor Only

**\$1.265** +вsт

Part No. 41000110C



3000W 4" C 330-360V DC

Motor Only

\$1,925 +gst

Part No. 43000330C



4CBW 2.2kW Motor 2200W 4" C AC/DC

Motor Only

\$2,100 + GST

Part No. 4CBW2.2MO



4CSS4-8 500W 4" C 48V DC

Submersible Pump & Motor

\$1.750 + GST

Part No. 40548



4CSS5-12 1000W 4" C 110V DC

Submersible Pump & Motor

\$**1.955** + GST

Part No. 41512



4CSS7-8 1000W 4" C 110V DC

Submersible Pump & Motor

\$1,955 + GST

Part No. 4178



4CSS12-6 1000W 4" C 110V DC

Submersible Pump & Motor

\$1,955 + GST

Part No. 41126



5CSS28-2 1000W 5" C 110V DC

Submersible Pump & Motor

\$1,955 + GST

Part No. 51282



\$2,960 +gst

Part No. 4CBW718

4CBW2.2 14-12 2200W 4" C AC/DC

Submersible Pump & Motor

\$2,960 +gst

Part No. 4CBW1412



4CBW2.2 19-17 2200W 4" C AC/DC

Submersible Pump & Motor

\$2,960 +gst

Part No. 4CBW1917



1500W Pool Pump and Motor

Pump & Motor Only

**\$1,350** +gst

Part No. 1500PM



500W Surface C Pump and Motor

Pump & Motor Only

**\$1,140** +gst

Part No. SSC3PM



## **Accessories**



## **Aluminium Bore Cap**



\$70 +GST

Part No. 6055



Tank Full Switch

Including 20m Cable

\$**165** +gst

Part No. 6101



**Pressure Switch** 

N/O N/C 12 Bar Gauge & Fittings

**\$275** +gsт

Part No. 6045NO



**Pressure Switch** 

N/O N/C 12 Bar

\$210 + GST

Part No. XMXA12L2135



**Dam Float** 

Suit 3" WATERBOY Pump

\$195 + GST

Part No. 6103



Dam Float

Suit 4" WATERBOY Pump

\$380 +GST

Part No. 6104



**Sacrificial Anode** 

3" HR

\$120 + GST

Part No. 6013



**Sacrificial Anode** 

4" HR

\$120 + GST

Part No. 6014



Sacrificial Anode 11/4"

4" Centrifugal

\$120 + GST

Part No. 6015



Sacrificial Anode 1½"
4" Centrifugal

h 4 0 0

\$120 + GST

Part No. 6016



1000V 32A DC Isolator

MC4 Connectors

\$160 + gst

Part No. ISOMC4



MC4 M&F Lead

2m

\$36 + GST

Part No. MC4/2M-S



**MC4 Branch Connector** 

Positive

\$35 + GST

Part No. CA-MC4-PP



**MC4 Branch Connector** 

Negative

\$35 +gst

Part No. CA-MC4-NS



**Double Acting Float Valve** 

11/4"



\$275 +GST

Part No. 6114



**Double Acting Float Valve** 

1½"

\$275 +GST

Part No. 6112



**Low Level Sensor** 



\$100 +GST

Part No. 1658



**Low Level Sensor** 

Fitted with 40m Cable

**\$160** + GST

Part No. 165840



## **Accessories**



#### CABLING (PER METER)

Add extra cabling to any package




















# Cable Splice & Wet Test (No discount applies) \$110 +GST Part No. 6500

#### **AC - DC POWER PACKS**









1300 554 307 sales@bwsolar.com.au accounts@bwsolar.com.au www.bwsolar.com.au